

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 1 of 14

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Base Gel Xtra

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Cosmetic product

Restricted to professional users.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	Wilde Cosmetics GmbH	
Street:	Rheingastr. 19a	
Place:	D-65375 Oestrich-Winkel	
Post-office box:	1220	
	D-65368 Oestrich-Winkel	
Telephone:	+49-6723-6020-0	Telefax: +49-6723-6020-15
e-mail:	beate.kerntopf@wilde-group.com	
Contact person:	Dr. Beate Kerntopf	Telephone: -752
<b>1.4. Emergency telephone number:</b>	+49-6723-6020-0 This telephone number is available during office hours only.	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

The classification is in compliance with coming legislation and therefore may differ from the safety label on the package.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

2-methylpropenoic acid, methacrylic acid

ethyl methacrylate

Signal word: Danger

Pictograms:



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Base Gel Xtra**

Print date: 11.03.2016

Product code: 2272

Page 2 of 14

**Hazard statements**

H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321	Specific treatment (see ... on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P352	Wash with plenty of water.
P363	Wash contaminated clothing before reuse.
P364	And wash it before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310	Immediately call a POISON CENTER/doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P370+P378	In case of fire: Use ... to extinguish.
P235	Keep cool.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to ....

**Special labelling of certain mixtures**

EUH208	Contains Isocyanates. May produce an allergic reaction. Restricted to professional users.
--------	--

**2.3. Other hazards**

Keep out of the reach of children. Harmful in contact with skin and if swallowed. Causes severe burns. Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 3 of 14

### Chemical characterization

Chemical Name / INCI:  
 Di-HEMA Trimethylhexyl Dicarbamate  
 Aliphatic Polyesterurethane Acrylate  
 Methacrylic Acid (2-methylpropenoic acid, methacrylic acid)  
 Ethyl Methacrylate (ethyl methacrylate)  
 Polyetherpolyol Tetraacrylate  
 Silica Dimethyl Silylate  
 Methyl Benzoylformate  
 BHT  
 p-Hydroxyanisole  
 Hydroquinone

### Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
79-41-4	2-methylpropenoic acid, methacrylic acid	15 - 25 %
	201-204-4	607-088-00-5
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A; H312 H302 H314	
97-63-2	ethyl methacrylate	5 - 10 %
	202-597-5	607-071-00-2
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H225 H319 H335 H315 H317	
51728-26-8	Polyetherpolyol Tetraacrylate	5 - 10 %
	500-111-9	01-2119969962-19
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411	
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol	<0,1 %
	204-617-8	604-005-00-4
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 10); H351 H341 H302 H318 H317 H400	

Full text of H and EUH statements: see section 16.

### Further Information

The classification is in compliance with coming legislation and therefore may differ from the safety label on the package.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Evacuate personnel to safe areas. Take off all contaminated clothing immediately. Consult a physician if necessary. Show this safety data sheet to the doctor in attendance.  
 If unconscious place in recovery position and seek medical advice.

#### After inhalation

Move to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

#### After contact with skin

In case of contact, immediately flush skin with soap and plenty of water. If skin irritation occurs, seek medical advice/attention. In case of accidental skin contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Base Gel Xtra**

Print date: 11.03.2016

Product code: 2272

Page 4 of 14

**After contact with eyes**

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.

In case of accidental eye contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of eye.

**After ingestion**

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No data is available on the product itself.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. In case of lung irritation, first treatment with dexametason aerosol (spray).

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture**

Polymerization can occur. Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers. Heating or fire can release toxic gas. Use water spray to cool unopened containers.

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

Keep away from sources of ignition - No smoking.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective suit. Use only explosion-proof equipment.

**Additional information**

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Evacuate personnel to safe areas. Use personal protective equipment. Keep away from sources of ignition - No smoking. Avoid breathing vapors, mist or gas. Avoid contact with skin and eyes.

**6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3. Methods and material for containment and cleaning up**

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Ensure adequate ventilation. Use explosion-proof equipment.

**6.4. Reference to other sections**

13. Disposal considerations

**SECTION 7: Handling and storage**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Base Gel Xtra**

Print date: 11.03.2016

Product code: 2272

Page 5 of 14

**7.1. Precautions for safe handling****Advice on safe handling**

Use only with adequate ventilation. Handle and open container with care. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas. Wash hands before breaks and at the end of workday. Handle in accordance with good industrial hygiene and safety practice. Take notice of labels and material safety data sheets for the working chemicals. Refer also to instructions for use.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Keep away from heat. May be ignited by open flame.

**Further information on handling**

Polymerisation occurs when exposed to white light, ultraviolet light or heat.  
Refer also to instructions for use.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Store in original container. Keep tightly closed in a dry, cool and well-ventilated place. Protect from frost, heat and sunlight. Keep at temperature not exceeding 40°C.

**Advice on storage compatibility**

Keep locked-up.

**7.3. Specific end use(s)**

Cosmetic product

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-31-9	Hydroquinone	-	0.5		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
79-41-4	Methacrylic acid	20	72		TWA (8 h)	WEL
		40	143		STEL (15 min)	WEL

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 6 of 14

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
79-41-4	2-methylpropenoic acid, methacrylic acid			
Worker DNEL, long-term		inhalation	systemic	29,6 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	6,55 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	6,3 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	88 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	4,25 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	2,55 mg/kg bw/day
97-63-2	ethyl methacrylate			
Worker DNEL, long-term		inhalation	local	267 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	10,8 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1 %
Worker DNEL, long-term		inhalation	systemic	370,5 mg/m <sup>3</sup>
Consumer , long-term		dermal	local	1 %
Consumer DNEL, long-term		dermal	systemic	6,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	189,8 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	76 mg/m <sup>3</sup>
51728-26-8	Polyetherpolyol Tetraacrylate			
Consumer DNEL, long-term		oral	systemic	0,3375 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	0,88 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	0,217 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			
Consumer DNEL, long-term		dermal	systemic	64 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	128 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	0,5 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	1,74 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	7 mg/m <sup>3</sup>

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 7 of 14

### PNEC values

CAS No	Substance	Value
Environmental compartment		
79-41-4	2-methylpropenoic acid, methacrylic acid	
Freshwater		0,82 mg/l
Soil		1,2 mg/kg
Marine water		0,82 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
97-63-2	ethyl methacrylate	
Marine water		1,8 mg/l
Freshwater		1,8 mg/l
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Freshwater sediment		40 mg/kg
Soil		1,47 mg/kg
51728-26-8	Polyetherpolyol Tetraacrylate	
Freshwater		0,00176 mg/l
Marine water		0,000176 mg/l
Freshwater sediment		0,017 mg/kg
Marine sediment		0,0017 mg/kg
Micro-organisms in sewage treatment plants (STP)		4 mg/l
Soil		0,0078 mg/kg
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol	
Micro-organisms in sewage treatment plants (STP)		0,71 mg/l
Freshwater sediment		0,00098 mg/kg
Marine sediment		0,000097 mg/kg
Freshwater		0,000114 mg/l
Marine water		0,0000114 mg/l
Soil		0,000129 mg/kg

### Additional advice on limit values

No data is available on the product itself.

### 8.2. Exposure controls

#### Appropriate engineering controls

Information about special precautions needed for bulk handling is available on request. Handle in accordance with good industrial hygiene and safety practice. To avoid risks to man and the environment, comply with the instructions for use.

#### Protective and hygiene measures

Provide sufficient air exchange and/or exhaust in work rooms. Handle and open container with care. Keep away from food, drink and animal feedingstuffs. Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately. Wash hands before breaks and at the end of workday.

#### Eye/face protection

Tightly fitting safety goggles

#### Hand protection

Use protective skin cream before handling the product.  
Nitrile rubber/Neoprene-Wear protective gloves.  
Break through time: >= 1 h

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 8 of 14

Glove thickness: 0,5 mm

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Replace when worn.

### Skin protection

Protective suit: Long sleeved clothing.

### Respiratory protection

Use only with adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

### Environmental exposure controls

The product should not be allowed to enter drains, water courses or the soil. Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic

#### Test method

### Changes in the physical state

Initial boiling point and boiling range:	116,5 °C
Flash point:	20-68 °C
Ignition temperature:	385 °C
Vapour pressure: (at 20 °C)	0,87 hPa
Vapour pressure: (at 50 °C)	8,2 hPa
Density:	1,08 g/cm <sup>3</sup>
Water solubility:	insoluble

### Solubility in other solvents

miscible with most organic solvents: Acetone, Alcohol

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data is available on the product itself.

### 10.2. Chemical stability

Keep containers tightly closed in a cool, well-ventilated place.

### 10.3. Possibility of hazardous reactions

Polymerization can occur.

### 10.4. Conditions to avoid

Extremes of temperature and direct sunlight. Exposure to light.  
Heat, flames and sparks.  
Polymerization can occur.  
Do not smoke.

### 10.5. Incompatible materials

Strong oxidizing agents, Strong acids and strong bases, Peroxides



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 9 of 14

#### **10.6. Hazardous decomposition products**

In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.  
Oxidizing and spontaneously flammable products.

### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

##### **Toxicokinetics, metabolism and distribution**

No data is available on the product itself.

##### **Acute toxicity**

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
79-41-4	2-methylpropenoic acid, methacrylic acid			
	oral	LD50 1320 mg/kg	rat	OECD Test Guideline 401
	dermal	LD50 > 500 mg/kg	rabbit	
	inhalative (4 h) vapour	LC50 7,1 mg/l	rat	OECD Test Guideline 403
97-63-2	ethyl methacrylate			
	oral	LD50 13424 mg/kg	rat	
	inhalative (4 h) vapour	LC50 55 mg/l	rat	
51728-26-8	Polyetherpolyol Tetraacrylate			
	oral	LD50 >2000 mg/kg	rat	OECD Test Guideline 401
	dermal	LD50 >2000 mg/kg	rat	OECD Test Guideline 403
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			
	oral	LD50 >300<600 mg/kg	Rat	OECD Test Guideline 401
	dermal	LD50 >2000 mg/kg	rabbit	OECD Test Guideline 402

##### **Specific effects in experiment on an animal**

No data is available on the product itself.

##### **Practical experience**

##### **Observations relevant to classification**

Health injuries are not known or expected under normal use.

### **SECTION 12: Ecological information**

#### **12.1. Toxicity**

No data is available on the product itself.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 10 of 14

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
79-41-4	2-methylpropenoic acid, methacrylic acid				
	Acute fish toxicity	LC50 85 mg/l	96 h	Oncorhynchus mykiss (rainbow trout)	
	Acute algae toxicity	ErC50 45 mg/l	72 h	Selenastrum capricornutum (green algae)	OECD Test Guideline 201
	Acute crustacea toxicity	EC50 >130 mg/l	48 h	Daphnia magna (Water flea)	
	Fish toxicity	NOEC 10 mg/l	35 d	Brachydanio rerio (zebra fish)	
	Crustacea toxicity	NOEC >53 mg/l	21 d	Daphnia magna (Water flea)	
97-63-2	ethyl methacrylate				
	Acute fish toxicity	LC50 100 mg/l	96 h	Oncorhynchus mykiss (rainbow trout)	OECD Test Guideline 203
	Acute algae toxicity	ErC50 >110 mg/l	72 h	Selenastrum capricornutum (green algae)	OECD Test Guideline 201
	Acute crustacea toxicity	EC50 >66 mg/l	48 h	Daphnia magna (Water flea)	OECD Test Guideline 202
	Fish toxicity	NOEC 28 mg/l	4 d	Oncorhynchus mykiss (rainbow trout)	OECD Test Guideline 203
	Algae toxicity	NOEC 110 mg/l	3 d	Selenastrum capricornutum (green algae)	OECD Test Guideline 201
	Crustacea toxicity	NOEC 41 mg/l	2 d	Daphnia magna (Water flea)	OECD Test Guideline 202
	Acute bacteria toxicity	(1000-1800 mg/l)	0,5 h		
51728-26-8	Polyetherpolyol Tetraacrylate				
	Acute fish toxicity	LC50 1,76 mg/l	96 h	Brachydanio rerio (zebra fish)	OECD Test Guideline 203
	Acute algae toxicity	ErC50 76,3 mg/l	72 h		
	Acute crustacea toxicity	EC50 90,94 mg/l	48 h	Daphnia magna (Water flea)	OECD Test Guideline 202
	Fish toxicity	NOEC 1,23 mg/l	4 d	Brachydanio rerio (zebra fish)	OECD Test Guideline 203
	Crustacea toxicity	NOEC 50 mg/l		Daphnia magna (Water flea)	OECD Test Guideline 202
	Acute bacteria toxicity	(>100 mg/l)	3 h		

### **12.2. Persistence and degradability**

No data is available on the product itself.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 11 of 14

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
79-41-4	2-methylpropenoic acid, methacrylic acid			
		86%	28	
	Readily biodegradable.			
97-63-2	ethyl methacrylate			
		77,4%	14	
	Readily biodegradable			
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			
		70%	14	
	Readily biodegradable.			

### 12.3. Bioaccumulative potential

No data is available on the product itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
97-63-2	ethyl methacrylate	1,25 - 1,94
51728-26-8	Polyetherpolyol Tetraacrylate	2,29

### BCF

CAS No	Chemical name	BCF	Species	Source
97-63-2	ethyl methacrylate	4,75		

### 12.4. Mobility in soil

No data is available on the product itself.

### 12.5. Results of PBT and vPvB assessment

No data is available on the product itself.

### 12.6. Other adverse effects

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Dispose of contents/container in accordance with local regulation.

#### Waste disposal number of waste from residues/unused products

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

#### Waste disposal number of used product

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

#### Waste disposal number of contaminated packaging

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 12 of 14


### Contaminated packaging

Dispose of contents/container in accordance with local regulation.


Solidify unexposed surplus and dispose of together with processed material as cured plastic waste.

## SECTION 14: Transport information


### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 3469
<b>14.2. UN proper shipping name:</b>	PAINT, FLAMMABLE, CORROSIVE (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3+8
	
Classification code:	FC
Special Provisions:	163
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	38
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 3469
<b>14.2. UN proper shipping name:</b>	PAINT, FLAMMABLE, CORROSIVE (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3+8
	
Classification code:	FC
Special Provisions:	163
Limited quantity:	5 L
Excepted quantity:	E1

### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 3469
<b>14.2. UN proper shipping name:</b>	PAINT, FLAMMABLE, CORROSIVE (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3+8
	
Special Provisions:	163, 223
Limited quantity:	5 L

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Base Gel Xtra

Print date: 11.03.2016

Product code: 2272

Page 13 of 14

Excepted quantity: E1  
EmS: F-E, S-C

### Air transport (ICAO)

**14.1. UN number:** UN 3469  
**14.2. UN proper shipping name:** PAINT, FLAMMABLE, CORROSIVE (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3+8



Special Provisions: A3 A72 A803  
Limited quantity Passenger: 1 L  
Passenger LQ: Y342  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 354  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 365  
IATA-max. quantity - Cargo: 60 L  
Danger releasing substance: No data is available on the product itself.

### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice. To avoid risks to man and the environment, comply with the instructions for use.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

#### Additional information

The classification is in compliance with coming legislation and therefore may differ from the safety label on the package.

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).  
Water contaminating class (D): 1 - slightly water contaminating

## SECTION 16: Other information

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H341 Suspected of causing genetic defects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Base Gel Xtra**

Print date: 11.03.2016

Product code: 2272

Page 14 of 14

H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Isocyanates. May produce an allergic reaction.

**Further Information**

All data refer to the product upon delivery

End Use: EG Directive 76/768/EEC (cosmetic regulation)

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

In case of emergency call CHEMTREC 1-800-424-9300.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*