according to Regulation (EC) No 1907/2006

### Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Sculpture - Sculpture F (all products)

Product group: Eigenprodukt

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Cosmetic product

Restricted to professional users.

### 1.3. Details of the supplier of the safety data sheet

Company name: Wilde Cosmetics GmbH Street: Rheingaustr. 19a Place: D-65375 Oestrich-Winkel

Post-office box: 1220

D-65368 Oestrich-Winkel

Telephone: +49-6723-6020-0 Telefax: +49-6723-6020-15

e-mail: beate.kerntopf@wilde-group.com

Contact person: Dr. Beate Kerntopf Telephone: -752

**1.4. Emergency telephone** +49-6723-6020-0 This telephone number is available during office hours only.

number:

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazard Statements: Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

The classification is in compliance with coming legislation and therefore may differ from the safety label on the

package.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

# Hazard components for labelling

Bis-GMA = ISOPROPYLIDENEDIPHENYL BISOXYHYDROXYPROPYL METHACRYLATE

PEG-4 Dimethacrylate

HYDROXYPROPYL METHACRYLATE

METHYL BENZOYLFORMATE

Signal word: Warning

Pictograms:



#### **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

according to Regulation (EC) No 1907/2006

### Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 2 of 11

H319 Causes serious eye irritation.

#### **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash Wash hands after handling, thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container to Offer surplus and non-recyclable solutions to a licensed

disposal company..

#### Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

### 2.3. Other hazards

Keep out of the reach of children. Irritating to eyes and skin. May cause sensitization by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

# **Chemical characterization**

Chemical Name / INCI:

Isopropylidenediphenyl Bishydroxypropyl Methacrylate

Aliphatic Polyesterurethane Acrylate

PEG-4 Dimethacrylate

Di-HEMA Trimethylhexyl Dicarbamate

Hydroxypropyl Methacrylate (3-hydroxypropyl methacrylate)

Polyetherpolyol Tetraacrylate Silica Dimethyl Silylate Methyl Benzoylformate

**BHT** 

p-Hydroxyanisole

[+/- CI 15850, CI 45410:2, Titanium Dioxide]

according to Regulation (EC) No 1907/2006

### Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 3 of 11

#### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regulati	on (EC) No. 1272/2008 [CLP]	•		
1565-94-2	Bis-GMA = ISOPROPYLIDENEDIP	HENYL BISOXYHYDROXYPROPYL	_ METHACRYLATE	25 - 50 %	
	216-367-7				
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.				
27813-02-1	HYDROXYPROPYL METHACRYLA		5 - 10 %		
	248-666-3		01-2119490226-37		
	Eye Irrit. 2, Skin Sens. 1; H319 H317				
15206-55-0	METHYL BENZOYLFORMATE			0,1 - 1 %	
	239-263-3		01-2120101338-67		
	Skin Sens. 1; H317				

Full text of H and EUH statements: see section 16.

#### **Further Information**

The classification is in compliance with coming legislation and therefore may differ from the safety label on the package.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

Evacuate personnel to safe areas. Take off all contaminated clothing immediately. Consult a physician if necessary. Show this safety data sheet to the doctor in attendance.

If unconscious place in recovery position and seek medical advice.

#### After inhalation

Move to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

#### After contact with skin

In case of contact, immediately flush skin with soap and plenty of water. If skin irritation occurs, seek medical advice/attention. In case of accidental skin contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.

#### After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.

In case of accidental eye contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of eye.

# After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data is available on the product itself.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

according to Regulation (EC) No 1907/2006

# Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 4 of 11

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Polymerization can occur. Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers. Heating or fire can release toxic gas. Use water spray to cool unopened containers.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

#### Additional information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Use personal protective equipment. Avoid breathing vapors, mist or gas. Avoid contact with skin and eyes.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3. Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4. Reference to other sections

13. Disposal considerations

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only with adequate ventilation. Handle and open container with care. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas. Wash hands before breaks and at the end of workday. Handle in accordance with good industrial hygiene and safety practice. Take notice of labels and material safety data sheets for the working chemicals. Refer also to instructions for use.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Keep away from heat. May be ignited by open flame.

# Further information on handling

Polymerisation occurs when exposed to white light, ultraviolet light or heat.

Refer also to instructions for use.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Store in original container. Keep tightly closed in a dry, cool and well-ventilated place. Protect from frost, heat and sunlight. Keep at temperature not exceeding 40°C.

# Advice on storage compatibility

not required

## 7.3. Specific end use(s)

Cosmetic product

according to Regulation (EC) No 1907/2006

# Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 5 of 11

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
27813-02-1	HYDROXYPROPYL METHACRYLATE					
Consumer DNEL, long-term inhalation systemic 8,8 mg/m³				8,8 mg/m³		
Worker DNEL	long-term	inhalation	systemic	14,7 mg/m³		
Worker DNEL	, long-term	dermal	systemic	4,2 mg/kg bw/day		
Consumer DN	EL, long-term	dermal	systemic	2,5 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	2,5 mg/kg bw/day		
51728-26-8	Polyetherpolyol Tetraacrylate					
Consumer DNEL, long-term		oral	systemic	0,375 mg/kg bw/day		
Worker DNEL	long-term	inhalation	systemic	0,88 mg/m³		
Worker DNEL	long-term	dermal	systemic	0,5 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	0,217 mg/m³		
Consumer DN	EL, long-term	dermal	systemic	0,25 mg/kg bw/day		
15206-55-0	METHYL BENZOYLFORMATE					
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day		
Consumer DNEL, long-term		dermal	systemic	1,67 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	1,67 mg/kg bw/day		

according to Regulation (EC) No 1907/2006

# Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 6 of 11

#### **PNEC values**

CAS No	Substance	
Environmenta	Il compartment	Value
27813-02-1	HYDROXYPROPYL METHACRYLATE	
Marine sedim	ent	6,28 mg/kg
Freshwater		0,904 mg/l
Soil		0,727 mg/kg
Marine water		0,904 mg/l
Freshwater se	ediment	6,28 mg/kg
51728-26-8	Polyetherpolyol Tetraacrylate	
Freshwater		0,00176 mg/l
Marine water		0,000176 mg/l
Freshwater se	ediment	0,017 mg/kg
Marine sedim	ent	0,0017 mg/kg
Soil		0,0078 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	4 mg/l
15206-55-0	METHYL BENZOYLFORMATE	
Freshwater		0,069 mg/l
Marine water		0,007 mg/l
Freshwater sediment		0,47 mg/kg
Marine sediment		0,047 mg/kg
Micro-organisms in sewage treatment plants (STP)		39 mg/l
Soil		0,027 mg/kg

## Additional advice on limit values

No data is available on the product itself.

### 8.2. Exposure controls

#### Appropriate engineering controls

Information about special precautions needed for bulk handling is available on request. Handle in accordance with good industrial hygiene and safety practice. To avoid risks to man and the environment, comply with the instructions for use.

#### Protective and hygiene measures

Provide sufficient air exchange and/or exhaust in work rooms. Handle and open container with care. Keep away from food, drink and animal feedingstuffs. Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately. Wash hands before breaks and at the end of workday.

#### Eye/face protection

Tightly fitting safety goggles

#### Hand protection

Use protective skin cream before handling the product.

Suitable material: Nitrile rubber/Neoprene-Wear protective gloves.

Break through time: >= 1 h Glove thickness: 0,5 mm

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Replace when worn.

according to Regulation (EC) No 1907/2006

### Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 7 of 11

#### Skin protection

Protective suit: Long sleeved clothing

#### Respiratory protection

Use only with adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

#### **Environmental exposure controls**

The product should not be allowed to enter drains, water courses or the soil. Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: viscous liquid
Colour: pigmented/colourless
Odour: characteristic

Test method

### Changes in the physical state

Initial boiling point and boiling range: > 200 °C

Flash point: > 100 °C

Ignition temperature: 355 °C

Vapour pressure: 0,11 hPa

(at 20 °C)

Density: 1,13 g/cm³
Water solubility: insoluble

#### Solubility in other solvents

miscible with most organic solvents: Acetone, Alcohol

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2. Chemical stability

Keep containers tightly closed in a cool, well-ventilated place.

### 10.3. Possibility of hazardous reactions

Polymerization can occur.

### 10.4. Conditions to avoid

Exposure to light. Keep away from direct sunlight. Do not expose to temperatures above 40 °C.

#### 10.5. Incompatible materials

Strong oxidizing agents, Strong acids and strong bases, Peroxides

#### 10.6. Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Toxicocinetics, metabolism and distribution

No data is available on the product itself.

according to Regulation (EC) No 1907/2006

# Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 8 of 11

### **Acute toxicity**

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
27813-02-1	HYDROXYPROPYL METHACRYLATE					
	oral	LD50	>2000 mg/kg		OECD Test Guideline 401	
	dermal	LD50	>5000 mg/kg	rabbit		
15206-55-0	METHYL BENZOYLFORMATE					
	oral	LD50	>6800 mg/kg		OECD Test Guideline 401	
	dermal	LD50	>2000 mg/kg		OECD Test Guideline 402	

# Specific effects in experiment on an animal

No data is available on the product itself.

#### **Practical experience**

# Other observations

Health injuries are not known or expected under normal use.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

No data is available on the product itself.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source			
27813-02-1	HYDROXYPROPYL METHA	HYDROXYPROPYL METHACRYLATE							
	Acute fish toxicity	LC50	85 mg/l	96 h	Oncorhynchus mykiss (rainbow trout)				
	Acute algae toxicity	ErC50	>97,2 mg/l	72 h		OECD Test Guideline 201			
	Acute crustacea toxicity	EC50	>143 mg/l	48 h	Daphnia magna (Water flea)	OECD Test Guideline 202			
	Crustacea toxicity	NOEC	45,2 mg/l	21 d	Daphnia magna (Water flea)				
15206-55-0	METHYL BENZOYLFORMATE								
	Acute fish toxicity	LC50	>54,6 mg/l	96 h	Brachydanio rerio (zebra fish)				
	Acute algae toxicity	ErC50	68,6 mg/l	72 h	Selenastrum capricornutum (green algae)				
	Acute crustacea toxicity	EC50	>39,6 mg/l	48 h	Daphnia magna (Water flea)				
	Crustacea toxicity	NOEC	>39,6 mg/l	2 d	Daphnia magna (Water flea)				
	Acute bacteria toxicity	(>1000 r	ng/l)	3 h					

### 12.2. Persistence and degradability

No data is available on the product itself.

according to Regulation (EC) No 1907/2006

### Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 9 of 11

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
27813-02-1	HYDROXYPROPYL METHACRYLATE				
		81%	28		
15206-55-0	METHYL BENZOYLFORMATE				
	Degradation	82%	10		
	Readily biodegradable.				

#### 12.3. Bioaccumulative potential

No data is available on the product itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
27813-02-1	HYDROXYPROPYL METHACRYLATE	0,97
15206-55-0	METHYL BENZOYLFORMATE	1,9

#### BCF

CAS No	Chemical name	BCF	Species	Source
27813-02-1	HYDROXYPROPYL METHACRYLATE	3,2		

#### 12.4. Mobility in soil

No data is available on the product itself.

#### 12.5. Results of PBT and vPvB assessment

No data is available on the product itself.

#### 12.6. Other adverse effects

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### Advice on disposal

Dispose of contents/container in accordance with local regulation.

### Waste disposal number of waste from residues/unused products

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

# Waste disposal number of used product

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

### Waste disposal number of contaminated packaging

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

### Contaminated packaging

Dispose of contents/container in accordance with local regulation.

Solidify unexposed surplus and dispose of together with processed material as cured plastic waste.

according to Regulation (EC) No 1907/2006

### Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 10 of 11

#### **SECTION 14: Transport information**

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Danger releasing substance: No data is available on the product itself.

### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice. To avoid risks to man and the environment, comply with the instructions for use.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

#### **Additional information**

The classification is in compliance with coming legislation and therefore may differ from the safety label on the package.

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 2 - water contaminating

# **SECTION 16: Other information**

### Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

according to Regulation (EC) No 1907/2006

# Sculpture - Sculpture F (all products)

Print date: 11.03.2016 Product code: 602 Page 11 of 11

H319 Causes serious eye irritation.

EUH204 Contains isocyanates. May produce an allergic reaction.

#### **Further Information**

All data refer to the product upon delivery

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. In case of emergency call CHEMTREC 1-800-424-9300.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)